

Passport easy^{plus} 422



Execution of this model :

- Split pot free standing fryer with two independent control panels
- Connection box of the heating elements made of coated die-cast aluminium, oil and water proof
- Easy to operate control panel with simple knob and 4 control lights
- Selection of the frying temperature in steps of 5°C, from 150°C up to 190°C
- Additional temperature control between 80 and 140 for the "Cooking Systems with Oil"
- Integrated fat melting cycle
- Standby function (energy-saving)
- Precise temperature control of +/- 1°C by a thermocouple
- Electronic safety thermostat with an independent circuit
- Deep drawn frying pot
- Heating elements with special draining and cleaning position
- 24V components on the operating side
- Two oil receptacles with coarse and fine filters
- Two stainless steel baskets
- Level of protection IPX 5

Technical specifications :

- | | |
|---------------------------------|---|
| ▪ Economic power consumption: | 2 x 7,5 kW – 4 Watt per cm ² |
| ▪ Tension: | 2 x 3NAC400V 50/60Hz |
| ▪ Fuse rating for 7,5 kW power: | 2 x 3 x 16 A |
| ▪ Supply line: | 2 x 3L+N+PE |
| ▪ Net weight without Options: | 69 kg |
| ▪ Capacity per basket: | 1,25 kg |
| ▪ Recommended basket load: | 0,9 kg |
| ▪ Output per hour: | 2 x 17 – 22 kg frozen chips
2 x 20 – 25 kg coolly stored chips |

Measurements :

- | | |
|-------------------|-----------------|
| ▪ Width: | 397,5 mm |
| ▪ Depth: | 650 mm |
| ▪ Working height: | 850 – 900 mm |
| ▪ Total height: | 943 – 993 mm |
| ▪ Oil content: | 2 x 7,5 – 9 lt. |

Optional extras :