

frifri aro SA

Chemin de St. Joux 7
CH-2520 La Neuveville
Tel +41 32 752 46 52
Fax +41 32 752 46 88
sales@frifri.com
www.frifri.com

Passport profi^{plus} 8+8



Execution of this model :

- Split pot table top fryer with two independent control panels
- Easy to operate control panel with simple knob
- Removable frying pot even if fitted with a drain valve for easy cleaning and maintenance
- Control lamps supervise temperatures and mains connection
- Integrated fat melting cycle
- Standby function (energy-saving)
- Selection of frying temperature by steps of 5°C, from 150°C up to 190°C
- Additional temperature control between 80 and 140 for the "Cooking Systems with Oil"
- Precise temperature control of +/- 1°C by a thermocouple
- Electronic working and safety thermostat
- Integrated protection against running without oil
- Special draining position
- Special decanting zone which ensures first quality frying and best efficiency
- Delivered with one large or two small frying basket per frying pot
- Level of protection IPX 3

Technical specifications :

- | | |
|---------------------------------|---|
| ▪ Power: | 2 x 6,9 kW |
| ▪ Tension: | 2 x 3NAC400V 50/60Hz |
| ▪ Fuse rating: | 2 x 3 x 10 A |
| ▪ Supply line: | 2 x 3L+N+PE |
| ▪ Net weight: | 26 kg |
| ▪ Capacity of the small basket: | 0,5 kg |
| ▪ Recommended basket load: | 0.35 kg |
| ▪ Output per hour: | 2 x 19 – 22 kg frozen chips
2 x 20 – 25 kg coolly stored chips |

Measurements :

- | | |
|----------------|-----------------|
| ▪ Width: | 720 mm |
| ▪ Depth: | 475 mm |
| ▪ Height: | 300 – 456 mm |
| ▪ Oil content: | 2 x 8 – 9,5 lt. |

Optional extras :

- Fritoil filter, finely meshed filter for oil cleaning