

## Passport vision 211

### Execution of this model :



- Full pot free standing fryer with single control panel
- Connection box of the heating elements made of coated die-cast aluminium, oil and water proof
- 20 user-configurable programs and four "Quick Access" buttons
- Selection of frying temperature degree by degree, from 30°C up to 190°C
- Advanced programming for "Cooking Systems with Oil"
- Integrated fat melting cycle
- Standby function (energy-saving)
- Precise temperature control of +/- 1°C by a thermocouple
- Electronic safety thermostat with an independent circuit
- Deep drawn frying pot without edges for a perfect cleaning
- Heating elements with special draining and cleaning position
- 24V components on the operating side
- Separate high tension connection box in the back of the fryer
- Two oil receptacles with coarse and fine filters
- One stainless steel baskets
- Level of protection IPX 5

### Technical specifications :

- |                                 |   |
|---------------------------------|---|
| ▪ Economic power consumption:   | 7,5 kW – 4 Watt per cm <sup>2</sup>                       |
| ▪ High power consumption I:     | 9 kW – 5 Watt per cm <sup>2</sup>                         |
| ▪ High power consumption II:    | 11 kW – 6 Watt per cm <sup>2</sup>                        |
| ▪ Tension:                      | 3NAC400V 50/60Hz  |
| ▪ Fuse rating for 7,5 kW power: | 3 x 16 A  |
| for 9 kW power:                 | 3 x 16 A  |
| for 11 kW power:                | 3 x 20 A  |
| ▪ Supply line:                  | 3L+N+PE   |
| ▪ Net weight without Options:   | 47 kg   |
| ▪ Capacity of basket:           | 1,25 kg   |
| ▪ Recommended basket load:      | 0,9 kg  |
| ▪ Output per hour:              | 17 – 22 kg frozen chips<br>20 – 25 kg coolly stored chips |

### Measurements :

- |                   |              |
|-------------------|--------------|
| ▪ Width:          | 197,5 mm     |
| ▪ Depth:          | 650 mm       |
| ▪ Working height: | 850 – 900 mm |
| ▪ Total height:   | 943 – 993 mm |
| ▪ Oil content:    | 7,5 – 9 lt.  |

### Optional extras :

- Fully integrated oil pump and filtration system
- Automatic basket lift
- The optional extra can only be delivered mounted, no separate delivery.