

Passport vision 411



Execution of this model :

- Full pot free standing fryer with single control panel
- Connection box of the heating elements made of coated die-cast aluminium, oil and water proof
- 20 user-configurable programs and four "Quick Access" buttons
- Selection of frying temperature degree by degree, from 30°C up to 190°C
- Advanced programming for "Cooking Systems with Oil"
- Integrated fat melting cycle
- Standby function (energy-saving)
- Precise temperature control of +/- 1°C by a thermocouple
- Electronic safety thermostat with an independent circuit
- Deep drawn frying pot without edges for a perfect cleaning
- Heating elements with special draining and cleaning position
- 24V components on the operating side
- Separate high tension connection box in the back of the fryer
- Two oil receptacles with coarse and fine filters
- Two stainless steel baskets
- Level of protection IPX 5

Technical specifications :

- | | |
|--------------------------------|---|
| ▪ Economic power consumption: | 15 kW – 4 Watt per cm ² |
| ▪ High power consumption I: | 18 kW – 5 Watt per cm ² |
| ▪ High power consumption II: | 22kW – 6 Watt per cm ² |
| ▪ Tension: | 3NAC400V 50/60Hz |
| ▪ Fuse rating for 15 kW power: | 3 x 25 A |
| for 18 kW power: | 3 x 25 A |
| for 22 kW power: | 3 x 32 A |
| ▪ Supply line: | 3L+N+PE |
| ▪ Net weight without options: | 72 kg |
| ▪ Capacity per basket: | 1,25 kg |
| ▪ Recommended basket load: | 0,9 kg |
| ▪ Output per hour: | 34 – 44 kg frozen chips
40 – 50 kg coolly stored chips |

Measurements :

- | | |
|-------------------|---------------|
| ▪ Width: | 397,5 mm |
| ▪ Depth: | 650 mm |
| ▪ Working height: | 850 – 900 mm |
| ▪ Total height: | 943 – 993 mm |
| ▪ Oil content: | 17 – 20,5 lt. |

Optional extras :

- Fully integrated oil pump and filtration system
- Automatic basket lift
- The optional extra can only be delivered mounted, no separate delivery.